



TECHNICAL DATA SHEET

GEM AGRI POWER 10W-30

A modern MP SUTO for use in latest generation high performance tractors.

Product Description:

GEM Agri Power 10w-30 is designed for use in engines, transmissions, hydraulics and final drives of modern tractors. The grade is blended from carefully selected base oils and the latest additive technology to produce a lubricant that exceeds the demands of latest generation Farm equipment.

Advantages/Benefits:

- Excellent low and high temperature stability
- Helps reduce wet brakes squawk
- OEM approved performance profile
- Suitable for most Agricultural & Plant machinery requirements
- Avoids PTO clutch slippage
- Compatible with all gaskets and seals

Application:

GEM Agri Power 10w-30 is suitable for use in both normally aspirated and turbo charged diesel and petrol engines. It can be used in transmission systems including those fitted with wet brakes, hydraulic systems, oil immersed clutches, gearboxes and final drives.

It is also suitable for use as a multi-purpose lubricant in many off Road or Plant hire applications.

For further information please contact your local representative or GEM Oils directly.



Typical Test data:

KV @40°C (cSt)	70.06
KV @100°C (cSt)	11.10
VI	149
TBN mg KOH/g	10.37
SG @ 15.6°C	0.880
Pour Point (°C)	-36
Flash point (°C)	202

Health & Safety: (Group 1)

Please refer to the relevant MSDS which is available to all customers.

Availability:

Available in bulk, 1000 litre IBC's, 200 litre barrels & 20 litre anti-glug drums.

Main Specifications:

SAE	10W-30
API	CF4/SF & GL4
Caterpillar	TO-2
Allison	C4
Ford	M2C 159B/C (SUTO)
	M2C 134D (UTTO)
New Holland	NH 024C/324B/410B
Massey Ferguson	M1139/1144 (SUTO)
	M1135/1141 (UTTO)
GIMA CMS	M1145 (UTTO/STO)
John Deere	J27 (SUTO), J20C (UTTO)
ZF	TE ML 06 B/C, 07 B
CNH MAT	3505/3525
Case	MS 1118/1207/1209



Gem Oils use a QMS system which is ISO 9001:2015 approved

Rev 002 Date 01.01.2020

Gem Oils Limited
Regaskin
Cavan H12 E4W2
Ireland
Tel +353 (0) 49 4331077
www.gemoils.ie