




TECHNICAL DATA SHEET

COMPRESSOR OIL 32

ISO VG32 Compressor Oil



Product Description:

Compressor Oil 32 is a superior grade compressor oil manufactured from low volatility mineral oil to give freedom from deposits caused by oil carry over.

Inhibitors are incorporated to control foaming, oxidation and to minimise mechanical wear.

Advantages/Benefits:

- Excellent oxidation stability
- Low volatility
- Low oil consumption & carry over
- Effective corrosion protection

Application:

Compressor Oil 32 is recommended primarily for the lubrication of rotary screw type compressors according to OEM recommendations.

For specific OEM recommendations please contact your local representative or GEM Oils directly.

Typical Test data:

KV @40°C (cSt)	32
KV @100°C (cSt)	4.7
VI	90 min
Appearance	Amber
SG @ 15.6°C	0.874
Pour Point (°C)	-12
Flash point (°C)	215

Health & Safety: (Group 1)

Please refer to the relevant MSDS which is available to all customers.

Availability:

Available in bulk, 1000 litre IBC's, 200 litre barrels and 20 litre drums.

Main Specifications:



Gem Oils use a QMS system which is ISO 9001:2015 approved

Rev 001 Date: 01.01.20

Gem Oils Limited
Regaskin
Cavan H12 E4W2
Ireland
Tel +353 (0) 49 4331077
www.gemoils.ie