



TECHNICAL DATA SHEET

FARMFLEET 15W-30

A Multi Purpose 15W-30 SUTO for use in turbo & non-turbo charged tractors.

Product Description:

Farmfleet 15W-30 is designed for use in engines, transmissions, hydraulics and final drives of most tractors. The grade is blended from carefully selected base oils and the latest additive technology to produce a lubricant that exceeds the performance demands of most Farm and Plant equipment.

Advantages/Benefits:

- Optimum viscosity stability
- Helps reduce wet brakes squawk
- OEM approved performance profile
- Suitable for most Agricultural & Plant machinery requirements
- Compatible with all gaskets and seals

Application:

Farmfleet 15W-30 is suitable for use in both normally aspirated and turbo charged diesel and petrol engines. It can be used in transmission systems including those fitted with wet brakes, hydraulic systems, oil immersed clutches, gearboxes and final drives.

It is also suitable for use as a multi-purpose lubricant in many off Road or Plant hire applications.

For further information please contact your local representative or GEM Oils directly.

Typical Test data:

KV @ 40°C (cSt)	82
KV @ 100°C (cSt)	11.4
VI	129
TBN mg KOH/g	9.4
SG @ 15.6°C	0.887
Pour Point (°C)	-30
Flash point (°C)	195
TBN	10

Health & Safety: (Group 1)

Please refer to the relevant MSDS which is available to all customers.

Availability:

Available in bulk, 1000 litre IBC's, 200 litre barrels & 20 litre plastic drums.

Main Specifications:

SAE	15W-30
API	CG-4 & GL4
Caterpillar	TO-2
Ford	M2C 159 B2/C
Massey Ferguson	M1145 (SUTO)
Massey Ferguson	M1143 (UTTO)
Allison	C4



Gem Oils use a QMS system which is ISO 9001:2015 approved

Rev 001 Date 01.01.20

Gem Oils Limited
Regaskin
Cavan H12 E4W2
Ireland
Tel +353 (0) 49 4331077
www.gemoils.ie