



Printing date 01.11.2024 Version number 1 Revision: 01.11.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Gem Synthetic LSX C5 0W-20
- · Registration number Mixture
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Product category PC24 Lubricants, greases, release products
- · Application of the substance / the mixture Lubricant
- · Uses advised against

Processes involving extreme heat use advised against.

Any use involving aerosol formation or vapour release in excess of the assigned Workplace Exposure Limit where workers are exposed without suitable Respiratory Protective Equpiment.

- · 1.3 Details of the supplier of the safety data sheet
- · Supplier:

Gem Oils Ltd

Regaskin

Cavan

Ireland

Tretatio

Tel: +353 (0) 49 4331077 Fax: +353 (0) 49 4368329

e-mail: productsafety@gemoils.ie

- · Further information obtainable from: Product safety department.
- · 1.4 Emergency telephone number:

National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week)

Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

IN NORTHERN IRELAND:

Members of the public should contact NHS Direct on 111.

SECTION 2: Hazards identification

- \cdot 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

EUH210 Safety data sheet available on request.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- \cdot **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: A blend of synthetic oils and highly refined mineral oils with multifunctional additives.

(Contd. on page 2)



Page 2/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31 as amended

Printing date 01.11.2024 Version number 1 Revision: 01.11.2024

Trade name: Gem Synthetic LSX C5 0W-20

(Contd. of page 1)

· Dangerous components:

Highly refined low-viscosity mineral oil**

♦ Asp. Tox. 1, H304

2.5 - 10%

· Additional information:

**Mineral oil may be described by one or more of the following: EC No. 265-157-1, Distillates (petroleum), hydrotreated heavy paraffinic; EC No. 265-169-7, Distillates (petroleum), solvent-dewaxed heavy paraffinic; EC No. 265-158-7, Distillates (petroleum), hydrotreated light paraffinic; EC No. 265-159-2, Distillates (petroleum), solvent-dewaxed light paraffinic.

Mineral oil contains <3% DMSO extract as measured by IP346.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Check for and remove any contact lenses.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Wash mouth out with water

Do not induce vomiting; call for medical help immediately.

If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

- · Information for doctor: Treat symptomatically and supportively.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Combustible

In case of fire, the following can be released:

Carbon monoxide (CO)

Sulphur Oxides (SOx)

Toxic metal oxide smoke

Phosphorous oxides

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Do not inhale explosion gases or combustion gases.

(Contd. on page 3)



Page 3/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31 as amended

Printing date 01.11.2024 Version number 1 Revision: 01.11.2024

Trade name: Gem Synthetic LSX C5 0W-20

(Contd. of page 2)

· Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Particular danger of slipping on leaked/spilled product.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Contain and collect spillage with non-combustible, absorbent material e.g.sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Prevent formation of aerosols.

Ensure good ventilation/exhaustion at the workplace.

Avoid direct contact (skin/eye contact, ingestion and/or inhalation of fume/mist/dust) with the product in the undiluted form

- · Information about fire and explosion protection: Do not heat up to temperatures close to flash point.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store in a bunded area.

- · Storage class: 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

\cdot Ingredients with limit values that require monitoring at the workplace:

Highly refined mineral oil**

OEL Short-term value: 5 mg/m³, 10 ppm Long-term value: 2 mg/m³, 4 ppm

Mineral Oil

(Contd. on page 4)





Printing date 01.11.2024 Version number 1 Revision: 01.11.2024

Trade name: Gem Synthetic LSX C5 0W-20

	(C	Contd. of page 3)
High	nly refined low-viscosity mineral oil**	
OEL	Short-term value: 5 mg/m ³ , 10 ppm	
	Long-term value: 2 mg/m ³ , 4 ppm	
	Mineral Oil	

· DNELs			
Highly ref	Highly refined mineral oil**		
Oral	Long-term systemic effects	740 μg/kg bw/day (general population)	
Dermal	Long-term systemic effects	970 μg/kg bw/day (worker)	
Inhalative	Long-term systemic effects	2.73 mg/m³ (worker)	
	Long-term local effects	1.19 mg/m³ (general population)	
		5.58 mg/m³ (worker)	
Highly ref	Highly refined low-viscosity mineral oil**		
Oral	Long-term systemic effects	740 μg/kg bw/day (general population)	
Dermal	Long-term systemic effects	970 μg/kg bw/day (worker)	
Inhalative	Long-term systemic effects	2.73 mg/m³ (worker)	
	Long-term local effects	1.19 mg/m³ (general population)	
		5.58 mg/m³ (worker)	

· PNECs

Highly refined mineral oil**

Secondary poisoning 9.33 mg/kg food

Highly refined low-viscosity mineral oil**

Secondary poisoning 9.33 mg/kg food

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment

Select PPE appropriate for the operations taking place taking into account the product properties.

· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Take note of assigned Workplace Exposure Limits.

Avoid contact with the eyes and skin.

Do not carry product impregnated cleaning cloths in trouser pockets.

Do not eat, drink, smoke or sniff while working.

Do not inhale gases / fumes / aerosols.

Wash hands before breaks and at the end of work.

- Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.
- · Hand protection



Protective gloves

Use gloves tested and approved under appropriate government standards such as NIOSH (US) or EN374 (EU).

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR



Page 5/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31 as amended

Printing date 01.11.2024 Version number 1 Revision: 01.11.2024

Trade name: Gem Synthetic LSX C5 0W-20

(Contd. of page 4)

Neoprene gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Break-through time: >480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Safety glasses with side-shields conforming to EN166.

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

· Body protection:



Protective work clothing

Body protection must be chosen depending on product properties, activity and possible exposure.

· Environmental exposure controls Do not allow to enter drains, sewers or watercourses.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Mild

Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.
 Boiling point or initial boiling point and boiling range Undetermined.
 Flammability Not applicable.

· Lower and upper explosion limit

Lower: 1 Vol %
 Upper: 7 Vol %
 Flash point: 195 °C
 Auto-ignition temperature: > 250 °C
 Decomposition temperature: Not determined.
 pH Not determined.

· pH · Viscosity:

• **Kinematic viscosity at 40** °C 38.6 mm²/s • **Dynamic:** Not determined.

· Solubility

• water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure:
 Not determined.
 Not determined.

· Density and/or relative density

• Density at 20 °C: 0.86 g/cm³
• Relative density Not determined.

(Contd. on page 6)



Page 6/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31 as amended

Printing date 01.11.2024 Version number 1 Revision: 01.11.2024

Trade name: Gem Synthetic LSX C5 0W-20

(Contd. of page 5)

	(Contd. of page 5)	
· Vapour density	Not determined.	
· 9.2 Other information	NOTE: The physical data presented above are typical values and should not be construed as a specification.	
· Appearance:	•	
· Form:	Fluid	
· Important information on protection of health ar	nd	
environment, and on safety.		
Ignition temperature:	Product is not self-igniting.	
· Explosive properties:	Product is not explosive. However, formation of explosive	
	air/vapour mixtures are possible.	
· Solvent content:		
· VOC (EC)	0.00 %	
· Change in condition		
· Evaporation rate	Not determined.	
· Information with regard to physical hazard classes		
· Explosives	Void	
· Flammable gases	Void	
· Aerosols	Void	
· Oxidising gases	Void	
· Gases under pressure	Void	
· Flammable liquids	Void	
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flammable gases		
in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- \cdot 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

At elevated temperatures, explosive vapour/air mixtures may be formed.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid Heat and static discharge.
- \cdot 10.5 Incompatible materials:

Strong acids.

Strong bases.

Strong oxidising agents.

· 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Phosphorus oxides (e.g. P2O5)

Sulphur oxides (SOx)





Printing date 01.11.2024 Version number 1 Revision: 01.11.2024

Trade name: Gem Synthetic LSX C5 0W-20

(Contd. of page 6)

Toxic metal oxide smoke

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:			
Highly ref	Highly refined mineral oil**		
Oral	LD50	> 2,000 mg/kg (rat)	
Dermal	LD50	> 5,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	> 20 mg/l (rat)	
Highly ref	Highly refined low-viscosity mineral oil**		
Oral	LD50	> 2,000 mg/kg (rat)	
Dermal	LD50	> 5,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	> 20 mg/l (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- $\cdot \textbf{Carcinogenicity} \ \text{Based on available data, the classification criteria are not met.} \\$
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- $\cdot \textbf{STOT-single exposure} \ \text{Based on available data, the classification criteria are not met.} \\$
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Subacute to chronic toxicity: Prolonged or repeated skin contact may irritate and cause dermatitis.
- · Additional toxicological information:

Prolonged and repeated contact with USED engine oils may cause serious skin disorders, including dermatitis and cancer. Engine oils are known to accumulate polycyclic aromatic hydrocarbons in use and there is evidence that used crankcase oils from petrol engines are carcinogenic to animals. Used engine oils fall within the definition of 'carcinogen'. Precautions advised by the Enforcing Authorities include controlling exposure by systems of work, personal protection and personal hygiene.

· 11.2 Information on other hazards

• Endocrine disrupting properties

None of the ingredients are listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability Not easily biodegradable
- 12.3 Bioaccumulative potential Contains components with the potential to bioaccumulate.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- \cdot 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.

(Contd. on page 8)





Printing date 01.11.2024 Version number 1 Revision: 01.11.2024

Trade name: Gem Synthetic LSX C5 0W-20

(Contd. of page 7)

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Recommended Hierarchy of Controls:

- Minimise waste;
- Reuse if not contaminated;
- Recycle, if possible; or
- Safe disposal (if all else fails).

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

Delivery of waste oil to offically authorised collectors only.

	· European waste catalogue		
		OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19)	
	13 02 00	waste engine, gear and lubricating oils	
Ī	13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils	

· Uncleaned packaging:

· Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Disposal must be made according to official regulations.

Containers, even those that are "empty," may contain residues that can develop flammable and/or hazardous vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information		
· 14.1 UN number or ID number · ADR/RID/ADN, ADN, IMDG, IATA	Not applicable	
· 14.2 UN proper shipping name · ADR/RID/ADN, ADN, IMDG, IATA	Not applicable	
· 14.3 Transport hazard class(es)		
· ADR/RID/ADN, ADN, IMDG, IATA · Class	Not applicable	
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	Not applicable	

(Contd. on page 9)



Page 9/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31 as amended

Printing date 01.11.2024 Version number 1 Revision: 01.11.2024

Trade name: Gem Synthetic LSX C5 0W-20

(Contd. of page 8)

	(Conta. or page o
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk according to IMO instruments Not applicable.	
· Transport/Additional information:	Not dangerous according to the above specifications.
· UN "Model Regulation":	Not applicable

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients are listed.
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients are listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients are listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients are listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients are listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients are listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

H304 May be fatal if swallowed and enters airways.

- · Department issuing SDS: Product safety department.
- · Date of previous version: 15.02.2024
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 10)



Page 10/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31 as amended

Printing date 01.11.2024 Version number 1 Revision: 01.11.2024

Trade name: Gem Synthetic LSX C5 0W-20

(Contd. of page 9)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.

IE —