



TECHNICAL DATA SHEET

HYDRAULIC OIL H150AW

A premium ISO VG150 Hydraulic Oil

Product Description:

GEM Hydraulic Oil H150AW is a superior grade hydraulic oil manufactured from low aromatic solvent refined base stocks with a naturally occurring high viscosity index.

The formulation contains a modern low zinc additive package which provides excellent anti-wear, anti-corrosion, anti-oxidant and anti-foam characteristics.

Hydraulic Oil H150AW provides excellent demulsification properties thus minimising the risk of hydrolysis in the presence of water.

Advantages/Benefits:

- Excellent demulsibility.
- Excellent air release.
- Low foaming.
- ISO cleanliness 15/12
- Superior anti-wear performance.
- High oxidation stability.
- Multifunctional use
-

Application:

Hydraulic Oil 150AW is suitable for most hydraulic power transmission systems where reciprocating, rotary and axial piston pumps are used. Typical applications will be found in static industrial and mobile earth moving hydraulics.

For specific OEM recommendations please contact your local representative or GEM Oils directly.



Typical Test data:

KV @40°C (cSt)	150.11
KV @100°C (cSt)	15.1
VI	101
Appearance	Clear and bright
SG @ 15.6°C	0.889
Pour Point (°C)	-12
Flash point (°C)	231

Health & Safety: (Group 1)

Please refer to the relevant MSDS which is available to all customers.

Availability:

Available in bulk, 1000 litre IBC's, 200 litre barrels and 20 litre anti-glug drums.

Main Specifications:

DIN 51 524-2: HLP
ISO 6743-4: HM
Denison HF 1, HF 2, HF 0
US Steel 127
Sperry Vickers I 286-S, M 2950-S,
AFNOR NF 48-600
VOMA 24318
Thyssen TH N-256132
SEB 181.222
CETOP RP 91 H
FZG Test, A/8.3/90: Load Stage 12



Rev 002 Date 27-11-2015

Gem Oils Limited
Regaskin
Cavan
Ireland
Tel +353 (0) 49 4331077
Fax +353 (0) 49 4368329