



TECHNICAL DATA SHEET

ROCK DRILL 150

Product Description:

Gem Rock Drill 150 is an extreme pressure treated rock drill and pneumatic lubricant. On pneumatic tools, due to the expansion of air, the temperature may be considerably lower than ambient. Gem Rock Drill 150 is formulated to be free flowing through airline lubricators and integral oilers under these conditions.

A second characteristic of air is that the relative humidity increases with decreasing temperatures, and unless the air has been specifically dried, water vapour will condense out into the working surfaces of the pneumatic tool. Gem Rock Drill 150 oil has been formulated to protect against corrosion and to withstand high pressures in sliding vane air motors. In all applications the importance of choosing the correct viscosity is emphasised to ensure maximum operating efficiency of equipment.

Application:

Exol Rock Drill 150 is designed for use in rock drills, jack hammers and other similar air operated tools

Typical Test Data:

SG @ 15.6°C	0.89
KV @ 40°C (cSt)	152.37
Flash Point COC (°C)	235

Availability:

Gem Rock Drill 150 is available in 200 litre barrels and 20 litre drums.

Health & Safety: (Group 2B)

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers



Gem Oils use a QMS system which is ISO 9001:2015 approved

Rev 001 Date 01.01.2020

Gem Oils Limited
Gem Oils Limited
Regaskin
Cavan H12 E4W2
Ireland
Tel +353 (0) 49 4331077
www.gemoils.ie