



TECHNICAL DATA SHEET

LAWNMOWER OIL

SAE 30W engine oil

Product Description:

Lawnmower Oil 30 is a monograde engine oil suitable for use in ride on, electric start and manual push lawnmowers. The oil is produced from high viscosity index mineral oils combined with an advanced additive package offering maximum protection to engines working under moderate to severe conditions.

Advantages/Benefits:

- Improved bore polishing protection.
- Suitable for use as Transmission oil in a variety of construction equipment.
- Superior anti-wear performance.
- Suitable for use in many engines of older design.
- Excellent sludge control.

Application:

Lawnmower Oil 30 meets a broad range of requirements imposed by international engine manufacturers including Briggs & Stratton and is suitable for use in most Honda, Ryobi, Mountfield, Hayter, Allen, Al-ko and Toro branded lawnmowers.

Lawnmower Oil 30 is also suitable for use in specified Allison and Caterpillar transmissions, torque converters and hydraulic oil in a wide range of construction equipment. Refer to OEM handbooks for exact specifications.

For further information please contact your local representative or GEM Oils directly.



Typical Test data:

KV @40°C (cSt)	99.9
KV @100°C (cSt)	11.66
VI	105
TBN mg KOH/g	9.20
SG @ 15.6°C	0.884
Pour Point (°C)	-30
Flash point (°C)	220

Health & Safety: (Group 1)

Please refer to the relevant MSDS which is available to all customers.

Availability:

Available in bulk, 1000 litre IBC's, 200 litre barrels, 20 litre drums, 1 gallon & 1 litres

Main Specifications:

SAE	30W
API	CE/SG
Caterpillar	TO2
Allison	C3
MAN	270, 271
MB	227.0, 227.1
Mack	EO-K
US Military	MIL-L-46152B
US Military	MIL-L-2104D



Gem Oils use a QMS system which is ISO 9001:2015 approved

Rev 001 Date 01.01.2020

Gem Oils Limited
Regaskin
Cavan H12 E4W2
Ireland
Tel +353 (0) 49 4331077
www.gemoils.ie