



TECHNICAL DATA SHEET

GEM CHAIN OIL SPECIAL

A tacky high viscosity non fling chain saw oil.

Product code: MBCWCHASP

Product Description:

Gem Chain Oil Special is a tacky high viscosity oil produced from highly refined base stocks treated with a non fling additive system.

Advantages/Benefits:

- Contains tackiness additive to keep the lubricant on the chain and lubricate effectively.
- Superior anti-wear performance.
- Good corrosion protection.
- Good pumpability.
- Excellent anti-fling properties.
- Compatible with all gaskets and seals.

Application:

- Chain saw cutter bars.
- Open roller chain lubrication.
- Roller bearing.
- General lubrication, where non drip characteristics required.

For specific recommendations please speak to your local GEM Oils representative or contact Gem Oils directly.

Typical Test data:

SAE	60
KV @40°C (cSt)	220
KV @100°C (cSt)	22
Appearance	Brown liquid
Neutralisation mg KOH/g	0.5 min
SG @ 15.6°C	0.891
Pour point	-10°C
Flash point (°C)	195 min

Health & Safety: (Group 1)

Please refer to the relevant MSDS which is available to all customers.

Availability:

Available in bulk, 1000 litre IBC's, 200 litre barrels, 20 litre drums and 4x4.5 litre packs.



Gem Oils use a QMS system which is ISO 9001:2015 approved

Rev 001 Date 01.01.2020

Gem Oils Limited
Regaskin
Cavan H12 E4W2
Ireland
Tel +353 (0) 49 4331077
www.gemoils.ie