



TECHNICAL DATA SHEET

SUPER UNIVERSAL OIL

Multi-Purpose 15W-30 SUTO for use in high performance tractors.

Product Description:

GEM SUTO 15W-30 is designed for use in engines, transmissions, hydraulics and final drives of most tractors. The grade is blended from carefully selected base oils and the latest additive technology to produce a lubricant that exceeds the performance demands of most Farm and Plant equipment.

Advantages/Benefits:

- Optimum viscosity stability
- Helps reduce wet brakes squawk
- OEM approved performance profile
- Suitable for most Agricultural & Plant machinery requirements
- High API Diesel specification
- Compatible with all gaskets and seals

Application:

GEM SUTO 15W-30 is suitable for use in both normally aspirated and turbo charged diesel and petrol engines. It can be used in transmission systems including those fitted with wet brakes, hydraulic systems, oil immersed clutches, gearboxes and final drives.

It is also suitable for use as a multi-purpose lubricant in many off Road or Plant hire applications.

For further information please contact your local representative or GEM Oils directly.

Typical Test data:

KV @40°C (cSt)	85
KV @100°C (cSt)	10.7
VI	125
TBN mg KOH/g	9.4
SG @ 15.6°C	0.883
Pour Point (°C)	-21
Flash point (°C)	260

Health & Safety: (Group 1)

Please refer to the relevant MSDS which is available to all customers.

Availability:

Available in bulk, 1000 litre IBC's, 200 litre barrels & anti-glug 20 litre drums.

Main Specifications:

SAE	15W-30
API	CG-4 & GL4
Caterpillar	T0-2
Ford	M2C 159B/C
New Holland	82009291
Massey Ferguson	M1139 (SUTO)
	M1143
	M1145 (UTTO)
John Deere	J27 (SUTO), J20C (UTTO)
ZF	TE ML 06B, 06C, 06L, 07B, 07D
Allison	C4



Gem Oils use a QMS system which is ISO 9001:2015 approved

Rev 001 Date 01.01.2020

Gem Oils Limited
Regaskin
Cavan H12 E4W2
Ireland
Tel +353 (0) 49 4331077
www.gemoils.ie