



TECHNICAL DATA SHEET

For further information please contact your local representative or GEM Oils directly.

SUPERFLEET 30W

Mixed fleet SAE 30W engine oil

Product Description:

Superfleet 30W is a mixed fleet monograde engine oil for both diesel and petrol engines. The oil is produced from high viscosity index mineral oils combined with an advanced additive package offering maximum protection to engines working under moderate to severe conditions.

Advantages/Benefits:

- Improved bore polishing protection.
- Suitable for use in turbo charged and naturally aspirated diesel engines.
- Suitable for use as Transmission oil in a variety of construction equipment.
- Superior anti-wear performance.
- Suitable for use in many engines of older design.
- Excellent sludge control.

Application:

Superfleet 30W meets a broad range of requirements imposed by international engine manufacturers. Typical applications are earth movers, general plant equipment, trucks, vans and taxis.

Superfleet 30W is also suitable for use in specified Allison and Caterpillar transmissions, torque converters and hydraulic oil in a wide range of construction equipment. Refer to OEM handbooks for exact specifications.



KV @40°C (cSt)	99.9
KV @100°C (cSt)	11.66
VI	105
TBN mg KOH/g	9.20
SG @ 15.6°C	0.884
Pour Point (°C)	-30
Flash point (°C)	220

Health & Safety: (Group 1)

Please refer to the relevant MSDS which is available to all customers.

Availability:

Available in bulk, 1000 litre IBC's, 200 litre barrels and 20 litre drums.

Main Specifications:

SAE	30W
API	CE/SG
Caterpillar	TO2
Allison	C3
MAN	270, 271
MB	227.0, 227.1
Mack	EO-K
US Military	MIL-L-46152B
US Military	MIL-L-2104D



Gem Oils use a QMS system which is ISO 9001:2015 approved

Rev 001 Date 01.01.20

Gem Oils Limited
Regaskin
Cavan H12 E4W2
Ireland
Tel +353 (0) 49 4331077
www.gemoils.ie