



TECHNICAL DATA SHEET

SUPERFLEET 40W

Mixed fleet SAE 40W engine oil



Product Description:

Superfleet 40w is a mixed fleet monograde engine oil for both diesel and petrol engines. The oil is produced from high viscosity index mineral oils combined with an advanced additive package offering maximum protection to engines working under moderate to severe conditions.

Advantages/Benefits:

- Improved bore polishing protection.
- Suitable for use in turbo charged and naturally aspirated diesel engines.
- Suitable for use as Transmission oil in a variety of construction equipment.
- Superior anti-wear performance.
- Suitable for use in many engines of older design.
- Excellent sludge control.

Application:

Superfleet 40W meets a broad range of requirements imposed by international engine manufacturers. Typical applications are earth movers, general plant equipment, trucks, vans and taxis.

Superfleet 20W is also suitable for use in specified Allison and Caterpillar transmissions, torque converters and hydraulic systems in a wide range of construction equipment. Refer to OEM handbooks for exact specifications.

For further information please contact your local representative or GEM Oils directly.

Typical Test data:

KV @40°C (cSt)	142.0
KV @100°C (cSt)	14.8
VI	104
TBN mg KOH/g	5.07
SG @ 15.6°C	0.888
Pour Point (°C)	-24
Flash point (°C)	220

Health & Safety: (Group 1)

Please refer to the relevant MSDS which is available to all customers.

Availability:

Available in bulk, 1000 litre IBC's, 200 litre barrels and 20 litre drums.

Main Specifications:

SAE	40W
API	CD/CE/SG
Caterpillar	E2
ACEA	C3



Gem Oils use a QMS system which is ISO 9001:2015 approved

Rev 001 Date 01.01.2020

Gem Oils Limited
Regaskin
Cavan H12 E4W2
Ireland
Tel +353 (0) 49 4331077
www.gemoils.ie