



## TECHNICAL DATA SHEET

### GEM GUARD SP 150

Industrial ISO VG 150 Gear Lubricant



#### Product Description:

Gem Guard SP 150 is an Extreme Pressure Heavy Duty Industrial Gear Oil providing exceptional EP performance and load carrying properties. Formulated from highly refined base oils and extreme pressure additives Gem Guard SP 150 protects against corrosion, has excellent water separating properties and is highly resistant to foaming in service

#### Advantages/Benefits:

- Excellent oxidation stability
- High level of EP performance
- Reduced micro-pitting
- Protects against corrosion
- Improved gear wear protection
- Good demulse properties

#### Application:

Gem Guard SP 150 is recommended for most types of enclosed gear applications. It is ideal for heavily loaded gear sets, including worm and industrial hypoid units and for gears which are subject to shock loading. It is also suitable for circulation or splash lubrication systems operating at peak temperatures of 120°C. It is also suitable for Chain Drives and Bearings.

For further information please contact your local representative or GEM Oils directly.

#### Typical Test data:

KV @40°C (cSt)	151.2
KV @100°C (cSt)	14.5
VI	98
Density @ 15°C	.893
Pour Point (°C)	-22
Flashpoint (°C)	249

#### Health & Safety: (Group 1)

Please refer to the relevant MSDS which is available to all customers.

#### Availability:

Available in bulk, 1000 litre IBC's, 200 litre barrels & 20 litres.

#### Main Specifications:

DIN	51517-3
ISO	6743-6 & 12925-1
AGMA	250.04 & 9005-D94
David Brown	S1 53.101
AGMA	9005/D94
Cincinnati Milacron	P-74 (C-220)
US Steel	224
Bosch Rexroth	Approved
Friedrich Flender	Approved
Müller Weingarten	Approved



Gem Oils use a QMS system which is ISO 9001:2015 approved

Rev 001 Date 01.01.2020

Gem Oils Limited  
Regaskin  
Cavan H12 E4W2  
Ireland  
Tel +353 (0) 49 4331077  
www.gemoils.ie