



TECHNICAL DATA SHEET

GEM GUARD SP 460

Industrial ISO VG 460 Gear Lubricant



Product Description:

Gem Guard SP 460 is an Extreme Pressure Heavy Duty Industrial Gear Oil providing exceptional EP performance and load carrying properties. Formulated from highly refined base oils and extreme pressure additives Gem Guard SP 460 protects against corrosion, has excellent water separating properties and is highly resistant to foaming in service

Advantages/Benefits:

- Excellent oxidation stability
- High level of EP performance
- Reduced micro-pitting
- Protects against corrosion
- Improved gear wear protection
- Good demulse properties

Application:

Gem Guard SP 460 is recommended for most types of enclosed gear applications. It is ideal for heavily loaded gear sets, including worm and industrial hypoid units and for gears which are subject to shock loading. It is also suitable for circulation or splash lubrication systems operating at peak temperatures of 120°C. It is also suitable for Chain Drives and Bearings.

For further information please contact your local representative or GEM Oils directly.

Typical Test data:

KV @40°C (cSt)	460
KV @100°C (cSt)	30.7
VI	96
Density @ 15°C	906
Pour Point (°C)	-12
Flashpoint (°C)	214

Health & Safety: (Group 1)

Please refer to the relevant MSDS which is available to all customers.

Availability:

Available in bulk, 1000 litre IBC's, 200 litre barrels & 20 litres

Main Specifications:

DIN	51517-3
ISO	6743-6
AISE	224
AGMA	9005-E02
David Brown	S1 53.101
Cincinnati Milacron	P-74 (C-220)
US Steel	224



Gem Oils use a QMS system which is ISO 9001:2015 approved

Rev 001 Date 01.01.20

Gem Oils Limited
Regaskin
Cavan H12 E4W2
Ireland
Tel +353 (0) 49 4331077
www.gemoils.ie